# Polyurethane thermal delay catalyst NT CATE-129 heat-sensitive metal catalyst

### Overview:

Name: Polyurethane thermal delay catalyst

Alias: heat-sensitive metal catalyst, polyurethane metal catalyst, metal catalyst, heat-sensitive metal catalyst, metal delay catalyst, strong gel catalyst, light foam catalyst, polyurethane heat-sensitive delay catalyst

NT CATE-129 is a strong gel catalyst, with strong selectivity to isocyanate-hydroxyl groups, good delay effect in this series of catalysts, and excellent hydrolysis resistance. When the material temperature is below 40  $^{\circ}$ C, the catalytic activity Very low, when the temperature of the material reaches 40  $^{\circ}$ C, its catalytic activity begins to appear, when the temperature of the material reaches 50  $^{\circ}$ C, its catalytic activity increases rapidly, and the temperature of the material reaches 110  $^{\circ}$ C, its catalytic activity is stronger than ordinary organic tin and organic bismuth on the market;

Thermosensitive metal catalyst Polyurethane metal catalyst Metal catalyst Thermal metal catalyst Metal delay catalyst Strong gel catalyst Light foam catalyst Polyurethane thermal delay catalyst



### use:

NT CATE-129 can be widely used in the production of urethane skates, single- and double-component sealants, paints, adhesives, etc., used in aliphatic isocyanates, will not make the product yellow.

## Storage and transportation:

It should be sealed and stored in a dry, cool and ventilated warehouse.

## package:

180KG/drum Storage: It is recommended to store in a dry and cool area with proper ventilation. After the original packaging, please fasten the packaging cover as soon as possible to prevent the water and other substances from mixing into the product and affecting its performance. Do not breathe dust, avoid skin and mucous membrane contact. Smoking, eating and drinking are prohibited in the workplace. After work,

shower and change clothes. Store contaminated clothing separately and wash it before reuse. Maintain good hygiene habits.

Company Name:	Newtop Chemical Materials (Shanghai) Co., Ltd.
Sales Manager:	Hunter
E_Mail:	Hunter@newtopchem.com
Tel:	+86 21-5161 9972
Mobile Phone:	+86-18301903153
Address:	Rm. 1104, No. 258, Songxing West Road, Baoshan District, Shanghai, China (Mainland)
Website:	www. newtopchem. com

## FAQ

Q1: May I get one sample before placing order?

Re: Yes, Sample are available. For normal products, samples are for free and you just need to bear the freight; For those high value products, you just need to freight and certain product cost. When we both cooperate for some times or when you are our VIP customer, free sample will be offered when you need.

Q2: Which payment is available for your company?

Re: T/T, L/C, You can choose the one which is convenient for you.

Q3: How and when can I get my goods after payment?

Re: For small quantity products, they will be delivered to you by international courier(DHL, FedEx, TNT etc.) or by air. Usually it will cost 3-5days that you can get the goods after delivery. For large quantity products, shipping by see is worthwhile. It will cost days to weeks to come to your destination port, which depends on where the port is.

Q4: Is there any possible to use my appointed label or package?

Re: Yes. If needed, we'd like to use label or package according to your requirement.

Q5: How can you guarantee the goods you offer is qualified?

Re: We always believe honesty and responsibility are basis of one company, so whatever products we provide for you all are qualified.